

## CABLE PREPARATION KIT FROM 50 TO 630 mm<sup>2</sup>

The tools in the ALR-CNPT / 630-1-MV-NG kit can be used to prepare cables from 50mm<sup>2</sup> to 630mm<sup>2</sup> in 12/20 kV.

For other voltages, check the diameter capacities of each tools of this kit.



### Characteristics

Application	MV kit
Diameter	16 - 58 mm
Section	50 - 630 mm <sup>2</sup>
Penciling tool	TC630
Dimensions L x l x h	575 x 470 x 145 mm
Weight	10 kg
Case	Plastic carrying case

### Ref.

### Contents of the kit

MF2/60	Multifunction tool for outer sheath and insulation
MF1+/60	Tool for bonded semiconductor and peelable with stylus
SRC-D	Scoring stylus for peelable semiconductor with transition chamfer
SCH	Chamfering stylus for insulation
ALROC-FENTE	Tool to perform slits on cable's outer sheath 25-630mm <sup>2</sup> 12/20kV
ROTO-TMG	Connector holder for bolted and clamping connections
GFE-TMG	Roller block for ROTO-TMG to tighten the outer sheath
K7/GRATT	Cartridge for sheath abrading, to be mounted on ROTO-TMG
EV/NPT	Tool to spread PE outer sheath with aluminium screen
EV630	Tool to spread PVC outer sheath with aluminium screen
LIGAREX	Clamping tool with return spring for straps
TC630	Penciling tool for insulation for 630mm <sup>2</sup> in 12/20 kV cables

